

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
NM 4160

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amini Oil Company	8. Farm or Lease Name Shell "B" State
3. Address of Operator 405 Wall Towers East - Midland, Texas 79701	9. Well No. 1
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>860</u> FEET FROM THE <u>East</u> LINE, SECTION <u>1</u> TOWNSHIP <u>17-S</u> RANGE <u>34-E</u> NMPM.	10. Field and Pool, or Wildcat N. Vacuum Abo
15. Elevation (Show whether DF, RT, GR, etc.) 4022 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-26-73 Drilled 7-7/8" hole to T.D. 8830'. Ran 270 jts. 5 1/2" 17# & 15.5# J-55 8rd lt&c casing to 8830' & cemented w/630 sx Halliburton lite & w/250 sx class C, 8 lbs. salt & 2/10 of 1% CFR-2 per sk. Plugged down @9:30 PM MST.

1-27-73 Temp. Survey. Top of cement 3200'; W.O.C. 24 hrs. - tested w/1000 psi for 30 mins. - held ok.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Karin Holman</u>	TITLE <u>Agent</u>	DATE <u>2-2-73</u>
APPROVED BY <u>Joe D. Ramey</u>	TITLE <u>Dist. I, Supv.</u>	DATE <u>FEB</u>
CONDITIONS OF APPROVAL, IF ANY		