

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30-025-24365
5. Indicate Type of Lease	STATE ☒ FEE ☐
6. State Oil & Gas Lease No.	B-867-1
7. Lease Name or Unit Agreement Name	Vacuum Grayburg San Andres Unit
8. Well No.	47
9. Pool name or Wildcat	Vacuum Grayburg San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☐ GAS WELL ☐ OTHER Injection

2. Name of Operator
Texaco Producing Inc.

3. Address of Operator
P.O. Box 730

4. Well Location

Unit Letter H : 1330 Feet From The North Line and 10 Feet From The East Line

Section 2 Township 18S Range 34 54E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
4003 GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER: ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 6-12-90 thru 6-25-90

- MIRV P.U. - back flow - NV BOP - TOH w/tbg & pkr - TIH w/ 3.875 bit, DC & WS, c/o to 4800'
- Spot 300 gal 4% NA Perborate across perms 4361 - 4739 TOH w/bit
- RV Rotary WL - perf guns found tight spot @ 1075'
- Swage csg @ 1075 - guns well not go - TIH w/pkr set @ 1500' - well head will not test - TOH
- TIH w/RBP set @ 1547 - repair wellhead - NV BOP - TIH w/tbg - TOH w/RBP
- RV WL - perf 4.5 csg w/2 JSPI @ 4403, 12, 20, 34, 46, 55, 96, 4512, 25, 50, 58, 81, 85, 4616, 46, 4712 (16 mt. 32 holes)
- Acidize perms 4361 - 4739 w/6000 gal 15% NEFE in 3 stages w/3000 lbs rock salt & 46 1.1 SG BS Max 1800, Nin 800 AIR 4 BPM, ISIP 900 15min 650
- TOH w/pkr TIH w/inj pkr & tbg - circ hole w/pkr fld set pkr @ 4280 test csg to 500# for 30 min

Prior 314 BWPD @ B20 pdi After 521 BWPD @ 1320 psi

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Richard DeSoto TITLE Engineering Technician DATE 7-28-90

TYPE OR PRINT NAME Richard DeSoto

TELEPHONE NO.

(This space for State Use)

APPROVED BY TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: