

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Corp  
P 1980  
Hobbs NM 88241

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

BTA Oil Producers

3. Address and Telephone No.

104 S. Pecos, Midland, TX 79701

(915) 682-3753

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 660' FWL

Sec 24, T18S, R32E

5. Lease Designation and Serial No.

NMNM 0392867

NM-93432

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Cinco de Mayo Fed #2

9. API Well No.

30-025-24562

10. Field and Pool, or Exploratory Area

Shinnery Queen

11. County or Parish, State

Lea Co., NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Proposed Procedure:

Set 4-1/2" CIBP @ 3900' w/35' cmt on top

Cut & pull 5-1/2" csg. est top of cmt @ 3500'

Spot 50 sx cmt plug 50' below 5-1/2" stub to 100' above 5-1/2" stub

Spot 75 sx cmt plug from 378' to 278' (10-3/4" shoe @ 328'). - Tag.

Spot 15 sx cmt plug @ surface.

Install dry hole marker.

{ Spot cement plug F/1090-1190' - Tag  
Spot cement plug F/2560-2660' }

RECEIVED  
1991 AUG 20 P 10:14  
ROSEBELL OFFICE

14. I hereby certify that the foregoing is true and correct

Signed

*Loepr Boyce*  
Royce D. Boyce

Title Operations Manager

Date 8/18/97

(This space for Federal or State office use)

FOR FEDERAL OFFICE USE ONLY

Approved by

Title

PETROLEUM ENGINEER

Date

Conditions of approval, if any: