

NO. COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-7990
7. Unit Agreement Name
8. Farm or Lease Name Jere
9. Well No. 2
13. Field and Pool, or Wildcat E. K. Yates, 7 Rvs., Qn.
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- Dry Hole
2. Name of Operator J. Cecil Rhodes
3. Address of Operator 822 Building of the Southwest, Midland, Texas
4. Location of Well UNIT LETTER B , 660 FEET FROM THE North LINE AND 1980 FEET FROM THE East LINE, SECTION 8 TOWNSHIP 18S RANGE 34E NMPM.
15. Elevation (Show whether DF, RT, CR, etc.) 4064 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cemented 8 5/8" Csg (24#) @ 355' w/300 Sxs. Circulated 49 Sxs to surface. After W.O.C.
12 hours tested Csg. 500 psi under B.O.P.S.
Drilled 7 7/8" hole to 4487' - No shows of oil or gas.
Dowell spotted cement plugs through drill pipe as follows:

4226' - 4126' - 35 Sx.
2960' - 2860' - 35 Sx.
1925' - 1825' - 35 Sx.
370' - 270' - 35 Sx.
S u r f a c e - 10 Sx.

Installed D. H. Marker - Prep to level surface. P & A 4-2-74

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <i>[Signature]</i>	TITLE Agent	DATE 6/21/74
APPROVED BY <i>[Signature]</i>	TITLE Oil & Gas	DATE MAR 17 1974
CONDITIONS OF APPROVAL, IF ANY:		