Form 9-331 (May 1963)			-	INTERIOF	SUBMIT IN TRIPLI (Other instructions verse side)	'E∙ re-	5. LEASE DESIGNATION	u No. 42-R1424. AND SERIAL NO.
GEOLOGICAL SURVEY SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)						NM-0554244 6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
1. OIL XX GAS WELL WELL	OTHER						7. UNIT AGREEMENT NA	ME
2. NAME OF OPERATOR							8. FARM OR LEASE NAME	
JOHN H. HILL							Edith Federal	
3. ADDRESS OF OPERATOR							9. WELL NO.	
313 E. Anderson Lane-Suite 332, Austin, Texas 78752							2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.)						10. FIELD AND POOL, OR WILDCAT		
At surface							Undesignated	
1980' from South line, 1980' from East line						11. SEC., T., R., M., CR BLK. AND SURVEY OR AREA		
<u> </u>							Sec. 23 T-18S	R-32E
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)					12. COUNTY OR PARISH	13. STATE
		377	77.7 Gr	<u>, 3787 KB</u>			Lea	New Mexico
16.	Check A	ppropria	te Box To	Indicate Natur	e of Notice, Report, o	or O	ther Data	
NOTICE OF INTENTION TO :					SUBSEQUENT REPORT OF:			
TEST WATER SHUT-		PULL OR A	LTER CASING		WATER SHUT-OFF	X	REPAIRING W	ELL
FRACTURE TREAT		MULTIPLE	COMPLETE		FRACTURE TREATMENT	x	ALTERING CA	SING
SHOOT OR ACIDIZE		ABANDON*			SHOOTING OR ACIDIZING	-	ABANDONMEN	T.
REPAIR WELL		CHANGE P	LANS		(Other)		· · · · · · · · · · · · · · · · · · ·	
(Other)					(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)			
17. DESCRIBE PROPOSED O proposed work. I nent to this work.)	i wen is unecu	ERATIONS (onally dril	Clearly state led, give sub	all pertinent det surface locations	ails, and give pertinent da and measured and true ve	tor	Including anti-	

Spudded 2-12-74. Drilled 11" hole to 380'. Set 8-5/8" 24# and 32# casing @ 380' w/250 sks Class H, 2% cc. Cement circulated. WOC 12 hrs, tested casing and BOP to 500#. Drilled 7-7/8" hole to 4270'. DST #1 Queen sand 3944-4266', tool open 90 min., recovered 180' of oil and gas cut mud. Set 4-1/2" 9.5# J-55 casing @ 4270', cemented w/300 sks posmix and Class H, 5# salt/sk. WOC 12 days. Tested casing to 3000#. Perforated Queen sand @ 3958, 3966, 3968, 3977, 3984 and 3987' and Penrose sand @ 4214, 4216, 4218, 4220, 4222 and 4224' (Total 12 holes). Acidized w/1000 gals. 15% acid, sand water fraced w/45,000# sand, 39,500 gals. gelled fresh water. Ran 2-3/8" tubing to 4225'. Testing.

18. I hereby certify that the foregoing is true and correct		
signed _ Querederteh	TITLE Superintendent	March 27, 1974
(This space for Federal or State office use)	TED FOR RECORD	
APPROVED BY	TITLE ACCEPTED FOR RECORD	Art
CONDITIONS OF APPROVAL, IF ANY:	APR 1 1914 ()4	TV III
*S	APR 1 1974 APR 1 1974 APR 1 SURVE HOBBS, NEW MEXICO HOBBS, NEW MEXICO	