

UNITED STATES **N. M. OIL & GAS COMMISSION**
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY **HOBBS, NEW MEXICO 88240**

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-93

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
1100 Wall Towers West, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface 1980' FNL 660' FEL, Sec. 18, T. 18 S., R. 33 E.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
West Corbin

9. WELL NO.
1

10. FIELD AND POOL, OR WILDCAT
(Wolfcamp)
Undes. South Corbin

11. SEC., T., E., M., OR BLE. AND SURVEY OR AREA
Sec. 18, T. 18 S., R. 33 E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3860' GR

12. COUNTY OR PARISH
Lea

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
(Other)
PULL OR ALTER CASING
MULTIPLE COMPLETE
ABANDON*
CHANGE PLANS

WATER SHUT-OFF
FRACTURE TREATMENT
SHOOTING OR ACIDIZING
(Other) Plugback to Wolfcamp
REPAIRING WELL
ALTERING CASING
ABANDONMENT*
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set cmt. retainer @ 12,050'. Sqz. perfs from 12,157 - 12,284' w/125 sxs. Class "H" cmt. Reverse out 30 sx. in csg. & 65 sxs. in perfs.
Perf. 4 JS @ 11,350'. Set cmt. retainer @ 11,330'. Sqz. w/150 sx. CL "H" cmt. @ 11,350'. PO of retainer. Reverse out 15 sxs. Displace hole w/2% KCL wtr. Run CBL from 11,322 to 10,150'. TOC @ 10,330'. Perf. 11,178' to 11,285'. Acdz. w/5000 gals. 15% NE acid 11,290' to 10,790'. Reverse acid out of csg. Set tbq. @ 10,992'. SN @ 10,953'.
Procedure approved 9-30-81 per Armando Lopez (USGS in Roswell, NM).

RECEIVED
JAN 27 1982

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct
SIGNED [Signature] TITLE Dist. Prod. Mgr. DATE 1-21-82

(This space for Federal or State office use)
ACCEPTED FOR RECORD
APPROVED BY PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:
JUN 14 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

TITLE _____ DATE _____

Instructions on Reverse Side

911