

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B 1113-1	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEFEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Marathon Oil Company		8. Farm or Lease Name Warn State A/C 2
3. Address of Operator P. O. Box 2409, Hobbs, New Mexico 88240		9. Well No. 17
4. Location of Well UNIT LETTER K, 1750 FEET FROM THE West LINE AND 2310 FEET FROM THE South LINE, SECTION 6 TOWNSHIP 18-S RANGE 35-E NMPM.		10. Field and Pool, or Wildcat Vacuum (Grybg.-San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 3989 K.D.B.		12. County Lea

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	
OTHER <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 4720' T.D. Ran 123 joints 5-1/2" casing, 17# and 20# Grade J-55 and N-80. Effective length 4710'. Set from 10' below K.D.B. to 4720' Last setting depth includes guide shoe and float collar. Cemented with 600 sacks light weight cement with 7-1/2# salt per sack, followed with 200 sacks of Class "C" cement. Had good returns while cementing. W.O.C. 48 hours. Tested B.O.P. and casing to 2000#. Tested O.K.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. A. Wilco TITLE Operations Superintendent DATE July 8, 1974

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: