

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR HILLIARD OIL & GAS, INC.		8. FARM OR LEASE NAME McELVAIN-FEDERAL	
3. ADDRESS OF OPERATOR 906 Building of the Southwest, Midland, Texas 79701		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FEL & 1980' FSL		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-18-S, R-34-E	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 3903' RKB 3921'		12. COUNTY OR PARISH Lea	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Set 4 1/2" Liner

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 8-22-74 Drilled well to 14,075' in Miss. Lime. Ran logs and elected not to drill on to Devonian. No commercial shows in Wolfcamp, Strawn, Atoka, Morrow or Miss. Lime. Elected to plug back and attempt completion in Bone Springs.
- 8-25-74 Plugged well back as follows:
50 sx cement plug 12,950 - 13,100'.
55 sx cement plug 10,300 - 10,450'.
75 sx cement plug 9,700 - 9,900'.
- 8-26-74 Drilled off cement plug to 9,650'.
- 8-27-74 Ran 4 1/2", 11.6#, K-55, casing as liner. Shoe @ 9649' with top of liner hanger @ 4870'. Cemented w/500 sx cement Class "H", 50-50 Pozmix, 2% gel, 8.6# salt/sx. Set liner hanger pack off. Tested csg w/1500# for 30 min., o.k.
- 9-7-74 Nippled up BOP's. Tested csg w/1500# for 30 min., o.k.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Manager of Operations

DATE

11-14-74

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
NOV 15 1974
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO