

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

1535 1/2

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator CONTINENTAL OIL COMPANY	8. Farm or Lease Name STATE B-19
3. Address of Operator Box 460, Hobbs, N.M. 88240	9. Well No. 1
4. Location of Well UNIT LETTER 0 662 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 19 TOWNSHIP 18S RANGE 37E N.M.P.M.	10. Field and Pool, or Wildcat Arkansas Junction San Andres & Goodwin Drinkard
15. Elevation (Show whether DF, RT, GR, etc.) 3745' GR.	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER Well Compl. ☒

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well was drilled to Goodwin Abo 7800'. Perf 5 1/2" csq 7564'-74 w/1 JSRF. Trtd w/3000 gal pad & 4000 gals acid. Swbd. dry. Squeezed w/150 sks cmt. Perf. 7194'-7200' & trtd w/2000 gals. acid. Perf 6934'-38' & trtd w/2000 gals acid. Perf 4710'-12', tested & squeezed w/150 sks cmt. Drld out cmt 4650'-4712'. Tested csq w/1000H, held ok. Perf w/1 JSRF @ 6230', 36', 42', 48', 54' & 6259'. Trtd w/1500 gals acid, then 1500 gal pad & 3000 gals acid. Perf 4718'-54' w/1 JSRF. Trtd w/1500 gal pad & 3000 gals acid. Swbd 100% wtr. Squeezed perfs 6230'-59 w/100 sks cmt. & 4718'.54' w/70 sks cmt. Held ok. (Perfs now open - 7194'-7200' & 6934'-38'). Perf 5 1/2" csq. @ 4613', 24' & 4630' w/2 JSRF. Trtd w/1500 gals acid. Drld. out cmt. retainer & cleaned out hole to 7234'. Pkr. set @ 6913'. Testing Drinkard perfs 6934'-38 & 7194'-7200'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE

DATE

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

NMACC - 21, File