

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
----------------------------	--

5. State Oil & Gas Lease No.

B-1535 1/2

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <u>temp. shut-in</u>	7. Unit Agreement Name
2. Name of Operator <b>CONOCO INC.</b>	8. Farm or Lease Name <u>State B-19</u>
3. Address of Operator <b>P. O. Box 460, Hobbs, N.M. 88240</b>	9. Well No. <u>1</u>
4. Location of Well UNIT LETTER <u>0</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>18S</u> RANGE <u>37E</u> NMPM.	10. Field and Pool, or Wildcat <u>Goodwin Drinkard</u>
15. Elevation (Show whether DF, RT, GR, etc.)	12. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

- ① MRO. POOH w/ tbg & rods.
- ② Spot 11 sxs class "C" w/ 2% CaCl<sub>2</sub> from 7250'-7144'.
- ③ Spot 12 sxs class "C" w/ 2% CaCl<sub>2</sub> from 4680'-4563'.
- ④ Perf @ 2895 w/ 4 JSPF circ. cmt to surface. Cmt Top @ 2750' in 5 1/2 csg in order to isolate the Yates.
- ⑤ Spot 10 sxs class "C" from 1650'-1550' to isolate the anhydrite.
- ⑥ Spot 100' plug @ surf csg shoe. Fill 8 5/8" x 13 3/8" annulus to surface via 1" pipe.
- ⑦ Spot 100' surface plug. Install P & A marker, clean location & rig down.
- ⑧ A proposed P & A sketch is attached.

A min CEMENT PLUG is 20 SK

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED DF FINNEY

TITLE Administrative Supervisor

DATE 12-3-86

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT 1 SUPERVISOR

APPROVED BY TR

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 5 1986

UNOCO-Hobbs(2) Fi

RECEIVED  
DEC 4 1986  
HOBBS OFFICE