

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-1505
7. Unit Agreement Name -
8. Farm or Lease Name Santa Fe
9. Well No. 129
10. Field and Pool, or Wildcat Vacuum Gb/San Andres
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Phillips Petroleum Company
3. Address of Operator Room 711, Phillips Bldg., Odessa, Texas 79761
4. Location of Well UNIT LETTER <u>E</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>990</u> FEET FROM THE <u>West</u> LINE, SECTION <u>5</u> TOWNSHIP <u>18-S</u> RANGE <u>35E</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) later

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cactus drilled 7 7/8" hole to 4850', reached at 9:30 a.m., 3-5-75. Conditioned hole, dresser Atlas ran BHC acoustic Gr Caliper and dual laterolog. Circ. hole. 3-6-75, set 121 jts (4839') 5 1/2" O.D. 17# N-80. LT&C csg. at 4839'. Howco cemented w/150 sx class H cmt w/40% DD, followed by 150 sx class H cmt 2/2# salt/sx. Plug to 4800', bumped w/1500#. Job comp. 8 a.m. 3-6-75. WOC 8 hrs, ran temperature survey, TOC outside csg at 2710'. Released rig, prep. to perf and test.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed W. J. Mueller TITLE Senior Reservoir Engineer DATE 3-10-75

APPROVED BY Only signed by TITLE Forney DATE

CONDITIONS OF APPROVAL, IF ANY: