

Proposed W. D. Grimes NCT-B #8

11/8/76

Sec 33 18-S 38-E

Lea Co. NM

H = 12'

13 $\frac{3}{8}$ " 48# H-40 @ 398'
w/ 450 sx circ.

2 strings 2 $\frac{3}{8}$ " 4.7# J-55

9 $\frac{5}{8}$ " 40# K-55 @ 3960'

w/ 1400 sx Hall. Light
200 sx C.I. C neat TOC 540'
grouted
150 sx C.I. C
to surface

Proposed Blinebry Perfs.

5844 - 5846

5872 - 5874

5932 - 5934

5954 - 5956

5991 - 5993

Parallel Tbg.
Anchor @ 5800'

Permanent Pkr. @ 6620'

Perf. Drk. w/ 4 - $\frac{1}{2}$ " JHPF

6654 - 6656

6684 - 6686

6730 - 6732

6756 - 6758

6787 - 6789

6848 - 6850

Cmt. retainer @ 6946'

Sqz. perfs @ 6956-57
w/ 43 sx

PB 6935

6964

7" 968' 23# K-55 top
6120' 23# N-80 bottom @ 7100'

w/ 150 sx C 6% gel
320 sx C .5% CFR 2 TSITOC 2510'

T.D. 7100'

RECEIVED

NOV 17 1976

OIL CONSERVATION COMM.
HOBBS, N. M.