

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI  
(Other instruction. n re-  
verse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 18302

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

McKay West Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Querecho Plains  
Bone Spring11. SEC., T., R., M., OR B.L. AND  
SURVEY OR AREA

S.34, T18S, R32E

12. COUNTY OR PARISH

Lea

13. STATE

New Mex.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

3. ADDRESS OF OPERATOR

9720 B Candelaria NE, Albuquerque, New Mexico 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' FNL &amp; 1980' FWL, Sec. 34, T18S, R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3706 GL

16.

## Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Recomplete in Bone Spring ☒  
(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Set 1.87" plug in "F" nipple in packer @ 12636'. Could not release on-off tool; could not unseat packer. Cut tubing @ 12628' /jet cutter; pulled tubing.
2. Set CIBP @ 12556'; dumped 35' cement on top of BP; new PBTD 12521'.
3. Ran 9727', 2-7/8" EUE N-80 tubing. Ran 1"-7/8"-3/4" combination rod string with 1 1/4" insert pump. Set Lufkin 640 unit, placed well on pump.

Note: Bone Spring perforations are: 8788-97; 9180-9204; 9220-30; 9886-9902 (previously perforated on original Morrow completion; never placed on production).

MORROW ZONE plugged 4-26-78

RECEIVED

JAN 15 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles W. Sanders

TITLE

Vice President

DATE

1/11/79

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD  
JAN 15 1979  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side