

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI
(Other instructions
verse side)

Form approved
Budget Bureau No. 42-R1424

LEASE DESIGNATION AND SERIAL NO.
NM 18302

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
2. NAME OF OPERATOR Petroleum Development Corporation		7. UNITED STATES NAME
3. ADDRESS OF OPERATOR 9720-B Candelaria N.E., Albuquerque, NM 87112		8. FARM OR RANCH NAME McKay-West Federal
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL & 1980' FWL Section 34-18S-32E		9. WELL NO. 1
14. PERMIT NO. --		10. FIELD AND POOL, OR WILDCAT Wildcat
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3706 GL		11. SEC. T., R., M., OR BLK. AND SURVEY OF AREA Sec. 34, T-18S, R-32E
		12. COUNTY OR PARISH Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) <u>Surface Casing</u>	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Commenced drilling operations @ 8:30 a.m. 2/14/75. Drilled 452', set 13-3/8", 54.5# K-55 casing @ 452'. Cemented with 250 sxs. Class "H" cement with 2% Gel & 2% CaCl and 150 sxs. Class "H" cement with 2% CaCl. P.D. @ 9:15 p.m. 2/14/75. Circulated over 100 sxs. cement. Pressure tested BOP and casing to 1000 psi for 30 minutes. Held O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Vice President

DATE 2/17/75

J. C. Johnson
(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

