

© Copyrighted Reproduction Prohibited

COUNTY	LEA	FIELD	Hobbs	STATE	NM
OPR	ESTES ENGINEERING CO.			API	30-025-25020
NO	1	LEASE	State	SERIAL	8-2-11 MN
	Sec 14, T-18-S, R-37-E			MAP	
	660' FSL, 660' FEL of Sec			CO-ORD	
	3 mi NW/Hobbs			ELEV	L.S.
SPD	5-15-75	CMP	6-25-75	WELL CLASS:	INIT D FIN DO
CSG	8 5/8" at 350' w/275 sx 4 1/2" at 4150' w/350 sx			FORMATION	DATUM
				FORMATION	DATUM
				FORMATION	DATUM
				FORMATION	DATUM
				FORMATION	DATUM
				FORMATION	DATUM
	TD 4150' (GRBG)			PBD	

IP (Grayburg) Perfs 4030-4126' P 19 BOPD + 36 BW. Pot based on 24 hr test. GOR 2718, Grav 33.4

CONTR	MGF	OPR'S ELEV	3690' KB	PD	4150' RT
-------	-----	------------	----------	----	----------

F.R. 5-5-75
 (Grayburg)
 5-20-75 Drlg 3098'
 5-28-75 TD 4150'; WOC
 6-3-75 TD 4150'; Prep Swab
 Perf (Grayburg) 4030-4126' w/10 shots (overall)
 Acid (4030-4126') 2500 gals
 Frac (4030-4126') 30,000 gals wtr + 50,000# sd
 6-10-75 TD 4150'; WO Pmp
 Swbd 6 BFPH (10% oil) (4030-4126')
 6-17-75 TD 4150'; WO Pmp
 6-25-75 TD 4150'; Prep TO Pmp
 7-1-75 TD 4150'; TO Pmp

8-2-11 NM

LEA
ESTES ENGINEERING CO.

Hobbs
1 State
Sec 14, T18S, R37E

NM
Page 2

7-7-75 TD 4150'; TO Pmp
Ppd 17 BO + 75% LW in 24 hrs (4030-4126')
7-14-75 TD 4150'; TO Pmp
7-22-75 TD 4150'; Prep Pot
7-28-75 TD 4150'; WO OCC Pot
Ppd 19 BO + 36 BW in 24 hrs (4030-4126')
8-4-75 TD 4150'; Complete
LOG TOPS: Anhydrite 1570', Salt 1680', Base
Salt 2678', Yates 2760', Seven Rivers 2862',
Queen 3236', Grayburg 3934'
8-9-75 COMPLETION ISSUED

8-2-11 NM