		Form C - 103 Supersedes Old						
FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103						
FILE		Effective 1-1-65						
U.S.G.S.		Sa. Indicate Type of Lease						
LAND OFFICE		State X Fee						
OPERATOR		5. State Oll & Gas Lease No.						
		E 5014						
SUND IDD NOT USE THIS FORM FOR PI USE "APPLICA								
I. OIL GAS GAS WELL	OTHER- Dry Hole	7. Unit Agreement Name						
2. Name of Operator	8. Farm or Lease Name							
Mesa Petroleum Co 3. Address of Operator	Peoples Vacuum							
904 Gihls Tower W								
4. Location of Well	10. Field and Pool, or Wildcat							
UNIT LETTERG	1980 FEET FROM THE NORTH LINE AND 1980 FEET FRO	Wildcat						
THE <u>East</u> Line, sect	TON <u>33</u> TOWNSHIP <u>18</u> RANGE <u>35</u> NMPK							
7//////////////////////////////////////	12. County							
	3896.9 KB 3883.9 GR	Lea AllIIII						
16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data								
NOTICE OF I	T REPORT OF:							
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING						
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT						
PULL OR ALTER CASING	CHANGE PLANS CASING TEST AND CEMENT JOB							
	OT HER							
OTHER								
17. Describe Proposed or Completed O work) SEE RULE 1103.	perations (Clearly state all pertinent details, and give pertinent dates, includin,	estimated date of starting any proposed						
Drilled 7-7/8" ho	le to 12,300' on 10-24-75. After running electri	cal logs, well was						
determined to be a	non commercial. Permission was obtained from New	Mexico Óil Con-						

servation (John Runyan) on October 24, 1975 to plug and abandon. Spotted cement
plugs as follows:
 40 sx cmt from 12,300'-12,170' at total depth and top of Miss Chester
 80 sx cmt from 11,600'-11,340' across top of Strawn
 40 sx cmt from 10,500'-10,370' across top of Wolfcamp
 40 sx cmt from 9,100'- 8,970' across top of 1st Bone Spring
 40 sx cmt from 7,500'- 7,420' across top of Bone Spring
 40 sx cmt from 4,800'- 4,670' across 8-5/8" csg shoe at 4737'
 Shot 8-5/8" csg at 698.50 and pulled. Recovered 675.85'.
 Spotted:
 75 sx cmt @ 744'-611' (top of stub @ 699')
 80 sx cmt @ 456'-360' (13-3/8" shoe @ 405')
 10 sx cmt @ surface - installed dry hole marker

Mud weight of 9.2 PPG between all plugs. Released rig at midnight 10-26-75. Plugged and abandoned.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.									
5 IGNED	Michael	P. Wonston	TITLE _	Division Engineer	DATE	October 31, 1975			
	01	\mathcal{A}			i.				
C ONDITIC	AT ATM A.		TITLE		DATE				

IC: JLF, LMC, MEC, WI Partners, NNOCC(3)