DEVIATION REPORT

Marathon-State No. 3 Section 12, T17S, R34E, Lea County, New Mexico

<u>DEPTH</u>	DEVIATION
394' 768' 1269' 1700'	1/2° 1/2° 1/2°
2086'	3/4°
2731'	1°
3218'	3/4°
3712'	1/2°
4010'	3/4°
4486'	3/4°
4968'	1 3/4°
5073'	1 1/2°
5623'	1/2°
6005'	3/4°
6170'	3/4°
6667'	1 1/4°
7032'	1 3/4°
7471'	1 1/4°
7941'	3/4°
8245'	1°
8750'	3/4° 3/4°

K. K AMINI

<9 X-

By: W. Glenn Burton Comptroller

STATE OF TEXAS

1

COUNTY OF MIDLAND &

The foregoing instrument was acknowledged before me this

25th day of <u>February</u>, 1976, by <u>W. Glenn Burton</u>

on behalf of <u>K. K. Amini</u>

Į

My Commission Expires September 10, 1977

Notary Public in and for Midland County Town

~1			
NO. OF COPIES RECEIVED			Form C-103
DISTRIBUTION			Supersedes Old
SANTA FE	NEW WEXICO DIL CONS	ERVATION COMMISSION	C-102 and C-103
FILE			Effective 1-1-65
U.S.G.S.			5a. Indicate Type of Lease
LAND OFFICE	—		State X Fee
OPERATOR			5. State Oil & Gas Lease No.
			B-2244
(DO NOT USE THIS FORM FOR PA USE "APPLICA	RY NOTICES AND REPORTS ON TO POSALS TO DRILL ON TO DEEPEN OR PLUG I TION FOR PERMIT -" (FORM C-101) FOR SUC	WELLS DACK TO A DIFFERENT RESERVOIR.	
1.			7. Unit Agreement Name
WELL WELL	OTHER-		
2. Name of Operator			8. Farm or Lease Name
K. K. Amini	Marathon-State		
3. Address of Operator			9. Well No.
P. O. Drawer 3068, Mi	3		
4. Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER 21	80 FEET FROM THE North	660 EE	North Vacuum Abo
THE West LINE, SECT	10 12 TOWNSHIP 17	S BANGE 34E	
	15. Elevation (Show whether		
	12. County		
	4030.1 GL		Lea
Check	Appropriate Bcx To Indicate N	ature of Notice, Report	or Other Data
	NTENTION TO:		QUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON		COMMENCE DRILLING CPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	
		OTHER	
OTHER			
			cluding estimated date of starting any proposed

1/6/76 - Mirt; spudded @ 5:00 P.M. 1/6/76

T.D. 390'; ran 14 jts. 12 3/4" 40.50# casing to 390', cemented with 450 sks. Class "C" with 1/4# Floseal and 2% CA CL 2 per sk. Plug down @ 2:30 A.M. 1/7/76, cement circulated, tested to 1000#; W.O.C. 12 hrs.

- 1/10/76 T.D. 3218'; ran 73 jts. 8 5/8" 32# & 24# casing to 3218', cemented with 750 sks. Howco Lite & with 250 sks. Class "C"; plug down @ 9:00 P.M. 1/10/76, tested to 1000#; W.O.C. 18 hrs.
- 1/29/76 T.D. 8750'; ran 213 jts. 4 1/2" 10.5# & 11.6# casing to 8750'; cemented with 800 sks. Howco Lite and with 250 cks. Class "C" 50/50 Pozmix. Plug down @ 2:45 P.M. 1/29/76; tested to 1000#; W.O.C. 24 hrs; prepare to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

. *

ł

SIGNED	Comptroller	DATE 2/5/76		
	Jerry Lozarz			11111
APPROVED BY	TITLE	DATE	.	
CONDITIONS OF APPE	ROVAL, IF ANY:			