

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
COPY TO O. C.

(Other Instructions on reverse side)

5. LEASE DESIGNATION AND SERIAL NO.

LC-069276

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

8. FARM OR LEASE NAME

Hudson Federal

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T18S, R33E

12. COUNTY OR PARISH

Lea NM

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Re-Entry

2. NAME OF OPERATOR

Robert N. Enfield

3. ADDRESS OF OPERATOR

P. O. Box 2431, Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface

660 FNL & 1980 FWL, Sec. 30, T-18-S, R-33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, or other)

3784.4 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Plug Back

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

2/19/80 Set Baker Cast Iron bridge plug at 13,100'. Dumped 35' cement on top of bridge plug.

Plugging operations to this point verbally approved by Mr. Stall.

Morrow formation plugged off.

18. I hereby certify that the foregoing is true and correct

SIGNED Robert N. Enfield

TITLE Operator

DATE 2/25/80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side