

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on
reverse side)COPY TO O. C. C.
Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-069276

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hudson-Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 30, T18S, R33E

12. COUNTY OR PARISH 13. STATE

Lea

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

Robert N. Enfield

3. ADDRESS OF OPERATOR

P. O. Box 2431, Santa Fe, New Mexico 87501

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660 FNL & 1980 FWL, Sec. 30, T-18-S, R-33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3784.4 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☒ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

T.D. 4820'.

Ran total 4753.00 (120 jts.) 9-5/8" casing as follows:

1077.79' (26 Jts.) 40.00#/ft. K-55 ST&C

43.34' (1 Jt.) 36.00#/ft. K-55 ST&C

217.63' (5 Jts.) 36.00#/ft. S-80 ST&C

2176.31' (58 Jts.) 36.00#/ft. K-55 ST&C

757.36' (18 Jts.) 40.00#/ft. K-55 ST&C

478.44' (12 Jts.) 40.00#/ft. N-80 ST&C

at 4820' with (1st Stage): 625 sx. Class "C" cement with 1/4# Flocele per sx.

(2nd Stage): 1700 sx. Halliburton Lite cement with 12# salt, 1/4# Flocele,
and 5# Gilsonite per sx.

Plug down 10:40 AM 8/20/76

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Operator

DATE 8/26/76

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
AUG 27 1976U. S. GEOLOGICAL SURVEY
HOBBBS, NEW MEXICO

RECEIVED

JUN 5 1976

U.S. CONSERVATION COMM.
HOBBS, N. M.