

NO. OF COPIES RECEIVED			
DISTRIBUTION			
SANTA FE			
FILE			
U.S.G.S.			
LAND OFFICE			
OPERATOR			

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
E - 1085

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- 2. Name of Operator Southern Union Supply Company 3. Address of Operator First International Bldg., Dallas, Texas 75270 4. Location of Well UNIT LETTER 0, 1980 FEET FROM THE East LINE AND 660 FEET FROM THE South LINE, SECTION 8 TOWNSHIP 17S RANGE 34E NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4105.5 GL	7. Unit Agreement Name 8. Farm or Lease Name Gallagher "8" State 9. Well No. 3 10. Field and Pool, or Wildcat North Vacuum 12. County Lea
--	---

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to 4755'. Ran 8 5/8", 24# & 32#, K-55, S+ & C casing to 4755' and cemented with 1900 Sacks Hallibuton Lite cement with 10 lbs. per sack salt and 1/4 lb per sack floccle and 200 sacks Class "C" cement with 2% calcium chloride. Plug down at 11:20 a.m. 10/11/76. Circulated 9 bbls. of cement. Nippled up and tested blind rams and casing to 1500 psig. for 30min. went in hole and tested pipe rams to 1500 psig for 30min. Drilled plugs at 12:01 a.m. 10/13/76.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED David A. Scholtz TITLE Drilling Engineer DATE 10-13-76

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE 10-13-1976

CONDITIONS OF APPROVAL, IF ANY: