

Form 9-331  
(May 1963)UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPlicate  
(Other instructions on  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <u>Salt Water Disposal</u>		5. LEASE DESIGNATION AND SERIAL NO. <b>NM-93</b>
2. NAME OF OPERATOR <u>Southland Royalty Company</u>		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -
3. ADDRESS OF OPERATOR <u>1100 Wall Towers West, Midland, TX 79701</u>		7. UNIT AGREEMENT NAME -
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <u>2310' FS&amp;EL, Sec. 18, T-18-S, R-33-E</u>		8. FARM OR LEASE NAME <u>West Corbin</u>
14. PERMIT NO.		9. WELL NO. <u>4</u>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <u>3840.4' GR</u>		10. FIELD AND POOL, OR WILDCAT <u>West Corbin Delaware</u>
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <u>Sec. 18, T-18-S, R-33-E</u>
		12. COUNTY OR PARISH <u>Lea</u>
		13. STATE <u>N.M.</u>

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) Start salt water injection ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

On 5-30-78 fractured perf 5032-62' w/20,000 gal gelled water; 20,000# 20/40 sand via 2 7/8" EUE tubing @ 25 BPM. POH w/tbg.  
Ran 162 jts 2 7/8" EUE 6.5# J-55 plastic coated tubing (Type TK-75) set @ 4996'. Ran Baker Model "AD" packer, set @ 4933'.

Date of first salt water injection June 13, 1978, at rate of 170 BPM on vacuum. NMOCC Order No. SWD-205.

RECEIVED

JUN 14 1978

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. Harvey Can

TITLE

District Engineer

DATE

6-14-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

A. D. L.

JUN 19 1978

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

\*See Instructions on Reverse Side