

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIP DATE*
(Other instruction
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

1100 Wall Towers West Bldg., Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2310' FSL & 2310' FEL, Sec. 18, T-18-S, R-33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3840.4'

5. LEASE DESIGNATION AND SERIAL NO.

NM 93

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

West Corbin

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

West Corbin Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 18

T-18-S, R-33-E

12. COUNTY OR PARISH

13. STATE

Lea

New Mexico

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set surface, test csg.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud well by LaRue Drilg. Co. 8:00 p.m. 2-4-78. Drill 12 1/4" hole to 340'.
Ran 12 jts 8-5/8" 24# K-55 ST&C Csg. Set @ 340'. Cmt w/250 sx Class "C"
cmt 28 C.C. Plug down @ 6:00 a.m. 2-5-78.
Circ cmt. 1/4" @ 340'.
WOC 12 hrs. Compressive strength 1350 psi @ casing shoe.
Test BOP and 8-5/8" csg @ 1000 psi for 30 min.-hold OK.
Drill ahead 7-7/8" hole.

Note: Change of operator from Aztec Oil and Gas Co. to Southland Royalty Company effective 1-1-78.

18. I hereby certify that the foregoing is true and correct

SIGNED

C. Harvey Can

TITLE District Engineer

DATE 2-7-78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

FEB 9 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO