

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

U. S. DEPT. OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
P.O. BOX 1000  
ROSEMBO, NEW MEXICO 88240

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Paloma Resources Inc.

3. Address and Telephone No.

P.O. Box 1814 Roswell, NM 88201-1814

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit N 1980' FWL & 660' FSL  
Sec. 34-T18s-R32e

5. Lease Designation and Serial No.

NM-67988

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Gulf-McKay Fed. #1

9. API Well No.

30-025-25471

10. Field and Pool, or Exploratory Area

Quefrehcho Plains ~~Pool~~

11. County or Parish, State

Lea, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent  
☐ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☒ Recompletion  
☒ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other

- ☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

RECOMPLETE TO BASAL BRUSHY CANYON DELAWARE ASAP

- 1). POH with rods and tubign.
- 2). Set CIBP + 35' cement @ 8450 over B.S. perfs 8503-35'.
- 3). Perf squeeze holes @ 7200'.
- 4). Recement with 125 lite and 300 "H". Cal. cement top of 5000'.
- 5). Perf Delaware at 6882-6902'.
- 6). Acidize and frac as required.
- 7). Hang back on pump and test.

14. I hereby certify that the foregoing is true and correct

Signed

Title AGENT

Date 9/03/92

(This space for Federal or State office use)

Approved by

Orig. Signed by [Signature]

Title

Date

9/15/92

Conditions of approval, if any:

**RECEIVED**

**SEP 16 1992**

**OCD HOBBS OFFICE**