

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O. C. C.

SUBMIT IN TRIPlicate
(Other instructions
verse side)

Form approved
Budget Bureau No. 43-R1424.

LEASE DESIGNATION AND SERIAL NO.
NM 25458

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

3. ADDRESS OF OPERATOR

9720 B Candelaria NE, Albuquerque, New Mexico 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' from the south line, 1980' from the west line, Sec. 34, T18S, R 32E.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3697 G.L.

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Gulf-McKay Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT
North Lusk-Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 34, T18S, R32E.

12. COUNTY OR PARTIAL STATE

Hobbs New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Surface casing.

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of operations completed on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Ran 9 jts. 13-3/8" 48# casing 407.70 set @ 400'. Cemented with 400 lb Class
2% gel., 2% CaCl₂. Plugged down @ 9:30pm, 3/5/77. Circulated out 80% cement
Tested BOP and casing to 1000 psi for 30".

Spudded 3-4-77

RECEIVED
MAR 9 1977
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

J. E. Johnson

TITLE

President

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
MAR 10 1977
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse

RECEIVED

DEC 11 1977

U.S. DEPARTMENT OF JUSTICE
FEDERAL BUREAU OF INVESTIGATION