

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

LC 058697B

6. If Indian, Allotment or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Conoco Inc.

3. Address and Telephone No.

10 Desta Drive W, Midland, TX 79705 (915)686-5424

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL SEC. ³⁰~~25~~, T-17S, R-³³~~32~~E UNIT 'M'

7. If Unit or CA, Agreement Designation

8. Well Name and No.

PEARL B NO. 7

9. API Well No.

3002525606

10. Field and Pool, or Exploratory Area

MALJAMAR GB SAN ANDRES

11. County or Parish, State

LEA, NM

CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☐ Subsequent Report

☒ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Perforation Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12-18-91
MIRU. GIH W/ BIT-SCRAPER - POH. GIH W/ CEMENT RETAINER - SET AT 4175.
PUMP 70 SKS CEMENT. 26 SKS BELOW RETAINER. SPOTTED 49 SX ON TOP OF RETAINER. TOC 3500'.
LOAD HOLE W/ P&A MUD. PUH TO 1320' SPOT 25 SX CEMENT PLUG 1320'-1075'. TAG TOC AT 965'.
LOAD HOLE W/ P&A MUD. SET 30 SX SURFACE PLUG (245'-SURFACE).

RIG DOWN
CLEANED LOCATION AND INSTALLED P&A MARKER.

Approved as to the accuracy of the well bore,
listing of well contents, and the well
surface logs and other data.

14. I hereby certify that the foregoing is true and correct

Signed

David H. Zankley

Title

SR. STAFF ANALYST

Date

5-8-92

(This space for Federal or State official use)

Approved by

David H. Zankley

Title

Date

5-15-92

Conditions of approval, if any:

RECEIVED

MAY 19 1992

CCD HOBBBS OFFICE