

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O.G.C.
SUBMIT IN TRIPLICATE*
(Other instructions
reverse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.

NM 24161

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Pedco-Gulf Federal Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

North Lusk-Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33, T18S, R32E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

3. ADDRESS OF OPERATOR

9720 B Candelaria NE, Albuquerque, New Mexico 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

660' from the east line; 1980' from the south line, Sec. 33,
T18S, R32E

14. PERMIT NO.

--

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3689 G. L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Surface Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Spudded 17-1/2" hole @ 11:30 am, 9/4/77. Ran 10 jts. 13-3/8" 48# H-40 casing, set
@ 410'; cemented with 300 sx. Class "H" 2% gel, 2% CaCl₂ and 150 sx. Class "H" w/2%
CaCl₂. Circ. out 50 sx. cement. Plugged down @ 5am, 9/5/77. Before drilling out,
tested casing 650 # for 30 "; held ok.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Secretary

DATE 9/7/77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
SEP 9 1977

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side