

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 12413-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

SUN McKAY FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Lusk-Morrow

11. SEC., T., R., M., OR B.L. AND

Sec. 10, T19S, R32E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

PETROLEUM DEVELOPMENT CORPORATION

3. ADDRESS OF OPERATOR

9720-B Candelaria, NE, Albuquerque, NM 87112

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)
See also space 17 below.)
At surface1730' from the west line, 1850' from the north line; Sec. 10,
T19S, R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3658 G. L.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Production Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 13,000' laying down drill pipe & collars, ran 252 jts. of 4½" 11.6# N-80, 8 rds. casing (10568') & 61 jts. 4½" 11.6# N-80 Butt. (2409') set @ 13,000' cemented with 300 sx. Class H, .08% Halad 22, .04% CFR-2, 3# KCL per sk., 1/4# Flocele per sk. 500 sx. HLC, .06% Halad 22, .04% CFR-2 5# KCL/sk. 1/4# Flocele per sk. Bumped plug @ 10:30 am, cemented, layed down drill pipe @ 6:00 pm, 12-26-77.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Secretary

DATE 12/29/77

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

ACCEPTED FOR RECORD

JAN 3 1978

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

RECEIVED

JAN 10 1978

OIL CONSERVATION COMM.
HOBBS, N. M.

7-1071A 8-2 01193-1A