

Proposed Development Plan for Surface Use

Amoco Production Company's Nellis Federal Well No. 2, Unit 0, Section 6, T-19-S, R-33-E.

1. Existing roads including location of exit from main highway.
Detailed map showing drillsite location in relation to the nearest town and all existing roads within one mile of the wellsite are shown on Exhibit A. From Hobbs, go southwest on Highway 62, 34.6 miles. Turn north on Road 176, and go 4.5 miles. Turn north at Potash Mine and go 6.1 miles. Turn east, and go 5.3 miles to West Tonto Battery. Turn north, and go .7 miles. Turn east, and go .5 miles to location. See Exhibits B and C.
2. Planned access roads.
From existing caliche road, the new road will go north to the southeast corner of the drilling pad. The new road will be 12' wide and 3,300' long. See Exhibit C.
3. Location of existing wells.
All existing wells within one mile radius are shown on Exhibit D.
4. Location of tank batteries and flow lines. Gas product taken at location. If well is a commercially productive gas well, a high pressure separator will be installed on south side of pad and gas connection will be made at separator vent. If well produces condensate or oil, a tank battery will be constructed at the location.
5. Location and type of water supply.
Fresh water will be piped from an existing water well 1-1/2 miles south of location and near the West Tonto Battery. Brine water will be trucked from Champion Brine Station.
6. Source of construction materials.
Caliche will be obtained from an existing caliche pit located approximately 1-1/2 miles southwest of location.
7. WASTE DISPOSAL -
 - a. Drill cuttings will be disposed of in the reserve pit.
 - b. Drilling fluids will be allowed to evaporate in the reserve pit until the pit is dry.

RECEIVED

JAN 9 1973

OIL CONSERVATION COMMISSION
HUBBS, LA 70454

- c. Trash, waste paper, garbage and junk will be burned or buried with a minimum of 24" cover. Waste material will be contained to prevent scattering by wind prior to ultimate disposal.
- d. Any produced water will be contained in tanks and be disposed of in an approved manner. Oil produced will be stored in tanks until sold, at which time it will be hauled from location.
- e. Current laws and regulations pertaining to disposal of human waste will be complied with.
- f. If productive, maintenance waste will be placed in special containers and buried or hauled away periodically.

8. ANCILLARY FACILITIES -

No camps, airstrips, etc., will be constructed.

9. WELLSITE LAYOUT -

- a. Size of Drilling Pad - 340' x 290' x 6"
- b. Compacted - Caliche
- c. Surfaced - No
- d. 450' square area around wellsite has been cleared by archeologist.
- e. See Exhibit E.

10. RESTORATION OF SURFACE -

Producing Well - all pits will be cut, filled, and levelled as soon as practical to original condition with rehabilitation to commence following removal of drilling and completion equipment. Rehabilitation to be completed in 180 days if possible.

Dry Hole - same as above with dry hole marker to be installed and surface reseeded if required.

11. OTHER INFORMATION -

- a. Terrain - Undulating plain with small depressions formed by wind and water erosion.
- b. Soil - Deep sand
- c. Vegetation - Scrub oak, mesquite, sage.
- d. Surface Use - Grazing.
- e. Ponds and Streams - None.
- f. Water Wells - None.
- g. Residences and Buildings - None.
- h. Arroyos, Canyons, etc. - None.
- i. Well Sign - Posted at drillsite.
- j. Open Pits - All pits containing liquid or mud will be fenced.
- k. Archaeological Resources - Drillsite which is in undulating plain, semi-arid, desert country, is in a low environmental risk area. The total effect of drilling and producing in this area would be minimal. No known archaeological, historical, or cultural sites exist in drill or road areas.

RECEIVED
JAN 2 1975

CL. SECRETARY COMM.
WASH. D. C.

12. OPERATOR'S REPRESENTATIVE -

Field personnel responsible for compliance with development plan for surface use is:

J. H. Hankins, Drilling Superintendent
P. O. Drawer A
Levelland, Texas 79336
Office Phone: 806-894-3163