

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR
PENNZOIL COMPANY

3. ADDRESS OF OPERATOR
P.O. Drawer 1828, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 2310' FEL, Sec 33, T17S
AT TOP PROD. INTERVAL: 4414' R33E
AT TOTAL DEPTH: 4490'

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE
Phillips Federal N.M. 801

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Phillips Federal

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Maljamar Grayburg/S.A.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec 33, T-17-S, R-33-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
4133 GR

RECEIVED
(NOTE: Report results of multiple completion or zone change on Form 9-330)

APR 14 1980

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8/6/80 Start to MI plugging unit.
8/7/80 Finish MI&RU
8/8/80 POH w/tbg. Set 5-1/2" CIBP on W.L. at 4375'. Could not get setting tool loose. Pulled W.L. in two near setting tool. Started in hole w/fishing tool on tbg.
8/9/80 Caught fish & POH w/tbg.
8/10/80 Shut down for Sunday.
8/11/80 RIH w/tbg & circulated hole w/salt gel. Spotted 16 sx cmt (100') on top of CIBP. Spotted 20 sx cmt from 1350-1450'. POH w/tbg.
8/12/80 Cut off wellhead, spotted 10 sx cmt at surface & installed marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED J. V. Culligan TITLE Operations Engineer DATE 8/13/80

APPROVED

(This space for Federal or State office use.)

APPROVED BY W. CHESTER DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NOV 5 1980

FOR

JAMES A. GILHAM
DISTRICT SUPERVISOR

See Instructions on Reverse Side