

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLI
(Other instructions
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 801

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

MAY 1978

2. NAME OF OPERATOR

Pennzoil Company

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

3. ADDRESS OF OPERATOR

P. O. Drawer 1828 - Midland, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

990' FNL & 2310' FEL of Sec. 33, T-17-S, R-33-E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

4133' G.L.

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Maljamar Grayburg-San Andres

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 33, T-17-S, R-33-E

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set production casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4-26-78 to 5-04-78

Drill from 355' to 4490'
Ran Logs

5-06-78

Ran 5 1/2" casing to 4490' w/D.V. tool at 1,410'.
Cemented 1st. stage w/650 sx. - WOC & circulated 4 hours.
Cemented 2nd. stage w/550 sx thru D.V. tool - Circulated out
118 sx. - Plug down at 1:15 A.M. (M.D.T.) 5-06-78. Set slips
& released rig.

Prep to complete.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Advanced Petroleum Engineer

DATE

5-08-78

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

DATE

MAY 1978

J. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side