

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	State ☒ Fee ☐
5. State Oil & Gas Lease No.	B-10784

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☐ GAS ☐ OTHER- PXA	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Firm or Lease Name State EX
3. Address of Operator P.O. Box 68, Hobbs NM 88240	9. Well No. 1
4. Location of Well UNIT LETTER E 1768 FEET FROM THE North LINE AND 990 FEET FROM THE West LINE, SECTION 3 TOWNSHIP 18-S RANGE 34-E NMPM.	10. Field and Pool, or Wildcat Vacuum GSA
15. Elevation (Show whether DF, RT, GR, etc.) 4040 RDB	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☒	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to PXA as follows:
POH with prod equip. RIH with CIBP and set at $\pm 4600'$. Cap CIBP with 35' Class C' neat. Displace hole with 112 bbls brine mud. Spot a 25 ex plug of Class C' neat from 1820'-1580'. Perf 6'19'-620' w/4 JSPF and establish circ. up 5 1/2" x 8 5/8" annulus. RIH and set cmt retainer at 380'. Pump 131 exs Class C' neat. Flush cmt to within 1/2 bbl of retainer, sting out, and dump excess on retainer. If circulation is not established: perf 479'-480' w/4 JSPF and
O&S NMOC, H 1-JRB 1-FJN 1-GCC

18. I hereby certify that the information above is true and complete, to the best of my knowledge and belief.

SIGNED Gary C. Clark TITLE Asst. Admin. Analyst DATE 12-11-84

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT ENGINEER TITLE DATE DEC 13 1984

CONDITIONS OF APPROVAL, IF ANY:

establish circulation up 8 5/8" annulus. Spot class C'neat from 620-490'. Set cmt retainer at 380' and pump 100 svs class C'neat. Flush to within 1/2 bbl of retainer. String out and dump excess on retainer.

Spot a 10 sv class C'neat surf plug from $\pm 96'$ to surf. Install PXA marker.

RECEIVED

OCT 10 1984

10/10/84