

Form 9-331  
Dec. 1973Form Approved.  
Budget Bureau No. 42-R1424UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Amoco Production Co.

3. ADDRESS OF OPERATOR

P. O. Box 68 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE:

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON\* ☐(other) ☐

SUBSEQUENT REPORT OF:

☐☐☒☐☐☐☐☐☐U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

5. LEASE

NM 077002

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Nellis Fed. "A" Gas Com

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

West Tonto Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

8-19-33

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3668' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in service unit 9-4-79. Ran cement retainer on wireline. Set at 13,155'. Ran Howco stinger and tubing. Squeezed perfs 13,183'-13,547'. Pumped 100 sacks Cl. 'H' cement. Reverse circulated 55 sacks. Ran 4-5/8" bit, drill collars, and tubing. Drilled cement retainer and cement from 13,163'-13,291'. Tested squeeze to 1000#, OK. Ran and set cast iron bridge plug at 13,270'. Spot 100 gallons 10% acetic acid. Perforated 13,183'-13,189' and 13,250'-13,260' swab tested. Fluid level 12,900' from surface. Well shut in. Well subsequently recompleted to Bone Springs.

ACCEPTED FOR RECORD

MAR 20 1980

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Ast. Adm. Analyst DATE 3-14-80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

0+4-USGS, H

1-Susp

1-MKE

1-Hou

1-Conoco

1-Superior

\*See Instructions on Reverse Side