

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-0188	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator		8. Farm or Lease Name	
Morris R. Antweil		Teapot	
3. Address of Operator		9. Well No.	
Box 2010, Hobbs, New Mexico 88240		1	
4. Location of Well		10. Field and Pool, or Wildcat	
UNIT LETTER <u>J</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM		Undesignated	
THE <u>East</u> LINE, SECTION <u>34</u> TOWNSHIP <u>18-S</u> RANGE <u>34-E</u> NMPM.		La Rica Morrow	
15. Elevation (Show whether DF, RT, GR, etc.)		12. County	
4000' GR		Lea	

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐

PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

TD 13,650' - 8-3/4" hole - Prep to P & A:

- Hole loaded w/10.5#/gal mud.
- 45 sx. (100') Cement plug 12,800' - 12,900' (top Morrow)
- 67 sx. (150') Cement plug 12,550' - 12,700' (Atoka water zone)
- 45 sx. (100') Cement plug 12,150' - 12,250' (top Canyon)
- 45 sx. (100') Cement plug 10,700' - 10,800' (top Wolfcamp)
- 45 sx. (100') Cement plug 6,700' - 6,800' (base San Andres)
- 45 sx. (100') Cement plug 5,150' - 5,250' (across 9-5/8" shoe)
- 45 sx. (100') Cement plug 1,670' - 1,770' (top anhydrite)
- 10 sx. surface plug.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rm Williams TITLE Agent DATE 3 August, 1978

APPROVED BY Orig. Signed By Jerry Sexton TITLE Dist 1, Supv. DATE AUG 7 1978

RECEIVED

AUG 4 1978

OIL CONSERVATION COMM.  
HOBBS, N. M.