

7. METHODS OF HANDLING WASTE DISPOSAL.

- A. Drill cuttings will be disposed of in the workover pit.
- B. Drilling fluids will be hauled off to the Loco Hills Water Disposal facility.
- C. Produced water during operations will be stored in workover pit until dry.
- 5 D. Oil produced during operations will be stored in tanks until sold.
- E. Current laws and regulations pertaining to the disposal of human waste will be complied with.
- F. Trash, waste paper, garbage and junk will be hauled to an approved dump site. All waste material will be contained to prevent scattering by the wind.
- G. All trash and debris will be removed from the wellsite within 30 days after finishing re:entry and or completion of operations.

8. ANCILLARY FACILITIES

None required.

9. WELLSITE LAYOUT.

Exhibit C shows the relative location and dimensions of the well pad, and workover pit.

10. PLANS FOR RESTORATION OF THE SURFACE.

- A. After finishing re:entry and completion operations, all equipment and other material not needed for further operations will be removed. The location will be cleaned of all trash and junk to leave the wellsite in as aesthetically pleasing a condition as possible.
- B. Unguarded pits, if any containing fluids will be fenced until they have been filled.
- C. If the proposed well is non-productive, all rehabilitation and or vegetation requirements of the BLM and USGS will be complied with and will be accomplished as expeditiously as possible. All pits will be filled and leveled within 90 days after abandonment.

RECEIVED

APR 11 1993

OFFICE
OF THE
DIRECTOR