

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well

2. NAME OF OPERATOR

Amoco Production Company

3. ADDRESS OF OPERATOR

P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL x 1980' FEL

AT TOP PROD. INTERVAL: (Unit j, NW/4, SE/4)

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐CHANGE ZONES ☐ABANDON* ☐(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

5. LEASE

NM - 01235-D

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Bondurant Federal

9. WELL NO.

5

10. FIELD OR WILDCAT NAME

West Tonto Wolfcamp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12-19-32

12. COUNTY OR PARISH

Lea

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3674 5' RDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

MAY 12 1983

OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface bearings and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved in service unit 3-23-83. Pulled rods and pump. Pumped 200 bbl brine water down tubing. Nippled up blowout preventer and pulled tubing and anchor. Set a cast iron bridge plug at 10750'. Capped with 35 sacks cement. Perforated at 450' with 4 JSPF. Loaded hole and broke circulation. Pumped 150 sacks cement and circ. to surface. Nippled down blowout preventer. Cut off well and installed PXA marker. Cut off anchors and moved out service unit 3-30-83.

4/17/83 called Amoco. Pete Mc Cray said a plug was spotted at at 5057' (25+X).

0+5-BLM,R

1-HOU

1-F.J.Nash, HOU

1-CLF

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Cathy L. Gorman TITLE ASST. ADM. ANALYST DATE 5-6-83

APPROVED

APPROVED (Orig. Sgd.) PETER W. CHESTER TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

NOV 17 1983

See Instructions on Reverse Side

RECEIVED
NOV 21 1983
C.C.D.
HOBBS OFFICE