Form	Approve	ed.	

UNITE!		. ATE	:S
DEPARTMENT	OF	THE	INTERIOR
GEOLOG	ICAL	. SUR	RVEY

5. LEASENM_077002	
NM_077002	
1	
6. IF INDIAN, ALLOTTEE OR TRIBE N	AME .
-	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME	***************************************
Nellis Federal B Gas C	om
9. WELL NO.	
1	
10. FIELD OR WILDCAT NAME	
Buffalo Penn Morrow	
11. SEC., T., R., M., OR BLK. AND SU	RVEY OR
AREA	
5-19-33	
12. COUNTY OR PARISH 13. STATE	
Lea NM	
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, A	ND WD)
3726 RDB	
7 2 3 3	<u> </u>
그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그	
Envilled Start & Start	
NOTE: Report results of multiple completi	on or zone

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.) 1. oil gas Ď well well other 2. NAME OF OPERATOR Amoco Production Company 3. ADDRESS OF OPERATOR P.O. Drawer "A", Levelland, TX 79336 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 AT SURFACE: 1980' FNL & 1980' FWL, Sec 5 AT TOP PROD. INTERVAL: (Unit F, SE/4 NW/4) AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE. REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING APR 27 1979 MULTIPLE COMPLETE CHANGE ZONES U. S. GEOLOGICAL SURVEY ABANDON* HOBBS, NEW MEXICO (other)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled to TD of 5,000' (4/23/79) and set 9 5/8" 36# K-55, J-55 and S-80 ST & C casing at 5,000'. Cemented with 200 sx Class H cement and 200 sx Class C cement. Cement did not circulate. Plugged down 8:40 a.m. 4/24/79. WOC 18 hours. Tested casing with 1000# for 15 minutes. Tested OK. Drilled cement 4925'-4945' and shoe 4948'-55'. Reduced hole to 8 3/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Ty	уре	Set @	Ft.
18. I hereby certify that the foregoing	is true and correct		
SIGNED Key Cox	TITLE Admin. Supervisor DATE	April 26, 1979	· · · · · · · · · · · · · · · · · · ·
- U	(This space for Federal or State office use)	33893 840	
APPROVED BY	TITLE DATE		•
CONDITIONS OF APPROVAL, IF ANY:		accust!	
0+4-USGS,H	TARREST STATES	All Kroning	
1-RWA	ACCOTED F	-70 hbh	

1-Susp

1-Houston

•See Instructions on Reverse Side 14 17 3

1. S. GEOLOGICAL SURVE HOBBS, NEW MEXICO.

FECEIVED

en de la companya de la co

MAY - 8 1979
OIL CONSERVATION COMM.