

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other2. NAME OF OPERATOR  
Amoco Production Company3. ADDRESS OF OPERATOR  
P.O. Drawer "A", Levelland, Texas 793364. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 1980' FWL, Sec 6  
AT TOP PROD. INTERVAL: (Unit F, SE/4, NW/4)  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

## SUBSEQUENT REPORT OF:

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐5. LEASE  
NM-077002

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Nellis Federal9. WELL NO.  
310. FIELD OR WILDCAT NAME  
Und. Buffalo Penn Morrow11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
6-19-3312. COUNTY OR PARISH  
Lea13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3699.7 GRRECEIVED  
MAR 3 1979(NOTE: Report results of multiple completion or zone change on Form 9-331-C)  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to TD of 5003' (2/28/79) and set 9 5/8" 36# K-55 and S-80 ST & C casing at 5003'. Cemented with 2380 sx BJ Lite with 5# Gilsonite and 1/4# Flocele and 8# salt per sx followed by 200 sx Class C with 2% CACL. Circulated 800 sx. Plugged down 12:45 p.m. 3/1/79. WOC 18 hours. Tested casing with 1500# for 30 minutes. Tested O.K. Drilled out 200' cement. Reduced hole to 8 3/4" and resumed drilling.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Ray Cox TITLE Admin. Supervisor DATE March 7, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:0+4-USGS,H  
1-Houston  
1-Susp  
1-RWA

\*See Instructions on Reverse Side

ACCEPTED FOR RECORD  
MAR 9 1979  
U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO