NI. OF COPIES RECEIVED	NEW MEXICO OIL CONSE	Form C-103 Supervedes Old C-102 and C-103 Effective 1-1-85	
SANTA FE FILE U.S.G.S. LAND OFFICE			Su. Indicate Type of Lease State State Foe 5. State Oil 6 Gas Leuse No.
OPERATOR	· · · · · · · · · · · · · · · · · · ·		B-1535- ¹ 2
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-1011 FOR SUCH PROPOSALS.)			7. Unit Agreement Name
VIL CAS Dry Hole			8. Farm or Lease Name
J. S. Abercrombie Mineral Co., Inc.			State 30
P. O. Box 27339, Houston, Texas 77027			1
4. Location of Well			10. Field and Pool, or Wildcar Undesignated
UNIT LETTER J 1980 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE, SECTION 30 TOWNSHIP 185 RANGE 37E NADA.			
THELUSULINE, SECT	15. Elevation (Show whether		12. County
	G.L. 37 <u>38</u>		Lea Alllilly
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
OTHER		OTHER	
17. Describe Fromesel of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of sturting any proposed work) SEE HULE 1103. Plugging operations started 3-6-79 Spotted Plug No.1 @ 7400'-7046' w/ 35 sx Class "c" w/ 2% CACL2. Tagged top of plug @ 6809' Respotted Plug No.2 @ 6900'-6548' w/ 35 sx Class "c" w/ 2% CACL2. Tagged top of plug @ 6809' Circulated well with 10#/Gal brine containing 25 lbs gel per barrel. Spotted Plug No.3 @ 6000'-5500' w/50 sx Class "c" w/ 2% CACL2. Tagged Plug @ 5101'. Spotted Plug No.3 @ 6000'-5500' w/ 50 sx Class "c" w/ 2% CACL2. Spotted Plug No.4 @ 5197'-5050' w/ 50 sx Class "c" w/ 2% CACL2. Spotted Plug No.5 @ 4470'-4329' w/ 50 sx Class "c" w/ 2% CACL2. Spotted plug No.6 @ 4100'-3951' w/ 50 sx Class "c" w/ 2% CACL2. Spotted plug No.6 @ 4100'-3951' w/ 50 sx Class "c" w/ 2% CACL2. Spotted plug No.6 @ 4100'-3951' w/ 50 sx Class "c" w/ 2% CACL2. Spotted Plug No.8 @ 1500'-1371' w/ 35 sx Class "c" w/ 2% CACL2. Spotted Plug No.9 @ Surface w/10 sx Class "c" w/ 2% CACL2. Installed Dry Hole Marker Plugging operations were witnessed by a representative of the NMOCC and were completed 3-12-79			
in. Thereby certify that the information above is true and complete to the best of my knowledge and belief. 4/18/79			
SIGNED R. J.	<i>lt</i> R.L. Felt, Pr	roduction Manager	DATE 7/10/75
ANTROVED BY L. A. Talta	mail mut		DATE

.

