

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O. C. S.

SUBMIT IN FIELD
(Other instructions
on reverse side)U. S. GEOLOGICAL SURVEY
Form 2-331, Rev. No. 42
LEASE DESIGNATION AND SERIAL
NM 2843A
6. IF INDIAN, ALLOTTEE OR TRIBAL

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)7. UNIT AGREEMENT NAME
SRM 1167 12/1/76

8. FARM OR LEASE NAME

Federal Com. 7

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

West Tonto Penn

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 7-T19S-R33E

12. COUNTY OR PARISH 13. STATE

Lea

NM

1. ☐ OIL
WELL ☐ GAS
WELL ☒ OTHER

2. NAME OF OPERATOR

INEXCO OIL COMPANY

3. ADDRESS OF OPERATOR

1100 Milam Bldg., Suite 1900, Houston, Texas 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL & 660' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3659.4

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Running Casing

(NOTE: Report results of multiple completion on Well
Completion or Completion Report and Log form.)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent data, including estimated date of start
proposed work. If well is directionally drilled, give subsurface locations and measured and true critical depths for all markers and zone
pertinent to this work.)*Set 13 3/8 48# H-40 STC @ 509.50'. Cemented with 335 sx 50/50 Pozmix & 150 sx Cl "C".
Cemented to surface.Set 8 5/8 0-2600 24# K-55 STC Cemented with 1st stage 1250 sx Lightweight with
2600-3500 24# S-80 STC 1/4lb per sack cello-flake tail in with 250 sxs
3500-5104 28# S-80 STC Class "C". Circulate between stages.
2nd Stage 550 sxs Lightweight with 1/4# Cello-Flake followed by 250 sxs Class "C".5 1/2" casing 13800-11038 17# JL-95 LTC Cemented with 125 sx Class "H" 50-50 Poz mix
11038- 1744 17# N-80 LTC 100 sxs Class "H".
1744- 0 17# JL-95 LTC

RECEIVED

MAY 25 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

K. C. Madley

TITLE Ass't. Drilling Administrator

DATE May 17, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

MAY 29 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

JUN 5 1973

[illegible]