

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form O-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API NO. 30-025-26222

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B 2148

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT TO DRILL OR TO DEEEN OR PLUG BACK TO A DIFFERENT RESERVOIR.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name
2. Name of Operator	8. Name of Lease Land
Phillips Petroleum Company	Leamex
3. Address of Operator	9. Well No.
Room 401, 4001 Penbrook Street, Odessa, Texas 79762	21
4. Location of Well	10. Field and Pool or Allotment
UNIT LETTER N 2310 FEET FROM THE West LINE AND 660 FEET FROM South THE North LINE, SECTION 22 TOWNSHIP 17-S RANGE 33-E N.M.P.M.	Leamex Paddock (ext)
15. Elevation (Show whether DF, RT, GR, etc.)	11. County
4150 GR RKB 4168	Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	
		OTHER <u>Total Depth</u> ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 7-7/8" hole to 6309', reached at 2:30 on 5-2-79.
Circulated to condition hole.

5-2-79 Schlumberger ran DLL-Micro-SFL, GR-FDC-CNL-CAL from TD to 2500' & GR-CNL-CAL 2500' to surface. TIH w/bit C&CM 3 hours.

5-3-79 Set 151 jts. 4-1/2" 11.60#, L-80, K-55 csg. @ 6309', float collar 6264' (total csg. 6315'). Cmt w/400 sxs TLW w/10% DD, 12# salt/sx, 1/4# Flocele/sx, 3# Gilsonite/sx. Tailed in w/150 sxs Class H w/8# salt/sx plug to 6264' w/7 bbls. 10% Acetic Acid & 90 bbls. 2% KCl wtr. Max psi 1200#. Bump plug 2000#. Csg reciprocated w/full returns. Set slips, cut off csg. ND BOP, clear pits. TOC by CBL @ 825', TD 6309'. Completed released rig @ 9:00 P.M. 5-3-79.

Correct TOC

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W.J. Mueller

TITLE Senior Engineering Specialist

DATE 5-15-79

Orig. Signed W.J. Mueller

APPROVED BY Jerry S. ...

TITLE ...

DATE ...

CONDITIONS OF APPROVAL, IF ANY:

Dist. ...

RECEIVED

MAY 17 1979

OIL CONSERVATION COMM.
HOUSTON, TEXAS