

COPY TO O. C. G.  
UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRI-  
(Other instruction  
verse side)ATE\*  
on re-Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0556094

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

--

7. UNIT AGREEMENT NAME

--

8. FARM OR LEASE NAME

PEDCO GULF FED. COMM.

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Undesig. N. Lusk Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 33, T18S, R32E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER ☐2. NAME OF OPERATOR  
PETROLEUM DEVELOPMENT CORPORATION3. ADDRESS OF OPERATOR  
9720 B Candelaria, NE, Albuquerque, New Mexico 871124. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface660' from the east line, 1980' from the north line, Sec. 33,  
T18S, R32E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3698 G. L.

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) Surface casing ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 8 am 6-22-79

Ran 10 jts., 419.04' of 13-3/8" 54.5# used casing, set @ 415'. Cemented with 300 sx. Class H (Howco) 2% gel, 2% CaCl<sub>2</sub>, plus 150 sx. Class H 2% CaCl<sub>2</sub>. Circulated out 150 sx. cement. Plug down @ 12:30 am 6/23/79. Tested casing to 700 psi for 30 min. before dlq. plug.

RECEIVED

JUN 26 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles W. Sanders

TITLE

Vice President

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

JUN 26 1979

U. S. GEOLOGICAL SURVEY  
HOBBS, NEW MEXICO

DATE

6-25-79

RECEIVED  
JUL - 6 1978  
Q.C.D. HOBBS, OFFICE

RECEIVED  
JUL - 6 1978  
Q.C.D. HOBBS, OFFICE