

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐ APR 13 1981

2. NAME OF OPERATOR
Inexco Oil Company Attn: A.W. Cook O. C. D.

3. ADDRESS OF OPERATOR
1100 Milam Bldg, Suite 1900, Houston, TX 77002 ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FNL + 1980' FEL

14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3656.5 GL

5. LEASE DESIGNATION AND SERIAL NO.

NM 9560-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal Sicola 12 Fed

9. WELL NO.

12-1

10. FIELD AND POOL, OR WILDCAT

W. Tonto Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 12, T19S-R32E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

COMPLETED OPERATIONS:

Killed well with 10.0 ppg Brine. Pulled tubing and Baker Lock-Set Packer. Ran CIBP to 10,050' & dropped 35' cement on top of plug. Made cut in 5 1/2" casing at 8,990' and jacked casing out of hole. Set 150' cement plugs from 9,060'-8,910', 7,510'-7,360', and 5,110'-4,960'. Place 100' cement plug at base of 13 3/8" casing. Cut 13 3/8" and 8 5/8" casing below surface and set 10 SX cement plug at surface. Installed dry hole marker and abandoned location.

** Well P & A 4-2-81 **

18. I hereby certify that the foregoing is true and correct

SIGNED

John R. Munson

TITLE Petroleum Engineer

DATE 4-7-81

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FOR

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1983-O-685229

847-485

U.S. DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
NATIONAL SYSTEM OF PUBLIC LANDS
WATER RESOURCES DIVISION

APR 20 '81

RECEIVED

MAY 18 1981

HOUSTON