

WELLBORE SKETCH AND WELL HISTORY

ELEV.: KB 3710 ", 17 ' ABOVE GL
3693'

LEASE & WELL NAME: UNIVERSITY FED. #1
FIELD: BOHE SPRINGS COUNTY: LEA ST.: NM
LOCATION: 1980 FSL & 1980 FWL
SEC 33 - 185 - 32E
DATE: 6-1-95 BY: DWS REV.: _____ BY: _____

CASING RECORD

SURFACE CASING

O.D.	WT/FT	GRADE	SET AT
<u>13 7/8</u>	<u>48 STK</u>	<u>H-40</u>	<u>400'</u>

PRODUCTION CASING

<u>8-5/8</u>	<u>32#</u>	<u>STK</u>	<u>A-55</u>	<u>4200'</u>
<u>5 1/2</u>	<u>STTS</u>	<u>17</u>	<u>LT4C</u>	<u>N-80 (2362)</u>
<u>5 1/2</u>	<u>32JTS</u>	<u>17</u>	<u>LT4C</u>	<u>J-55 (1354)</u>
<u>5 1/2</u>	<u>10JTS</u>	<u>15.5</u>	<u>LT4C</u>	<u>J-55 (4168)</u>
		<u>17</u>	<u>LT4C</u>	<u>A-55 (541)</u>

TUBING

NO. JTS.	O.D.	THD.	TYPE	WT.	GDE.	SET AT
	<u>2 7/8</u>	<u>EUE880</u>			<u>N-80</u>	<u>8432</u>

WELL HISTORY:

7-11-79 COMPL MORROW

1ST 3460# 656 MCF 4/64

2nd 3320# 914 MCF 5/64

3rd 3120# 1307 MCF 7/64

4th 2818# 1884 MCF 10/64

PUMP COMA (6-7-83)

PUMP LFT (12-83)

PXA 12889-12895 (6-85)

PERF 12610-12688 x PXA w/ CIBP @ 11100

PERF WLC 10520-585 (7-85)

PXA WLC (10-88)

RECOM. BOHE SPR. CIBP @ 10450 w/ 35'

CIRC CMT w/ 370 SX TAIL 325 SX LEAD

TOC BY TEMP 4500' EST TOP OF TAIL 7100'

PERF 8446-8470 8482-8496

1.0" FIBERGLASS ROGS w/ 7/8" STEEL ROGS BTM
QTY NOT KNOWN

HOLE SIZE: 17 1/2 "
TOC: CIRC

13 7/8 " • 400 "
CMT 500 SX

HOLE SIZE: 12 1/4 "
TOC: STRT "
CIRC.

8 5/8 " • 4200 "
CMT 1700 SX

10-88 TOC BY WL 4500'

HOLE SIZE: 7 7/8 "
TOC: 9900 ' BY WL TEMP.

8446-8470 8482-8496 PBD 8596'
CENT RET @ 8600 x BLK SQ 702690
8650-52 CMT 3Q HOLES

CIBP @ 10450 w/ 35' CMT PBD 10415
10520-585

CIBP @ 11100 w/ 35' CMT PBD 11065'
PERF 12610-12688

CIBP @ 12815 w/ 15' CMT

M&L @ 5 1/2 BAKER @ 12820'

12889-12895

5 1/2 " • 13045 "
CMT 850 SX

TD: 13045 ' PBD: 12930 '