

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-2948

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator
REX ALCORN
Address of Operator
Ingram Building, 100 So. Kentucky, Roswell, New Mexico 88201
Location of Well
UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1930 FEET FROM THE East LINE, SECTION 20 TOWNSHIP 18 S RANGE 36 E N.M.P.M.

7. Unit Agreement Name
8. Farm or Lease Name
Bobbi
9. Well No.
1-Y
10. Field and Pool, or Wildcat
Ark. Junct.-Penn
12. County
LEA

15. Elevation (Show whether DF, RT, GR, etc.)
3832' GR 3848' KB

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input checked="" type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	
		OTHER Plug Back to W. Ark. Junction-SA <input checked="" type="checkbox"/>	

16. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to plug back and re-complete in West Arkansas Junction-San Andres Zone at 5474-80 feet without pulling 5 1/2" casing. Current producing perfs at 10,863-933', lower Penn sand.

Pull rods, pump, tubing and anchor. Set cast iron bridge plug at about 10,700 feet with 35 feet cement spotted on top plug. Top Cement behind 5 1/2" casing is at 10,200 feet by temperature survey. Perforate 4 holes at 5700 feet, run cement retainer and squeeze with 300 sax Class C Halliburton cement. Run collar locator and cement bond log. Perforate 5474-80, acidize, sand frac, swab and complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rex Alcorn TITLE Operator DATE 2-28-81

APPROVED BY Don L. Smith TITLE Don L. Smith DATE 2-28-81
CONDITIONS OF APPROVAL, IF ANY: