

NO. OF COPIES RECEIVED	
DISTRIBUTION	
STATE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

API No. 30-025-26394

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO REOPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT - M (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Phillips Petroleum Company

Address of Operator
Room 401, 4001 Penbrook Street, Odessa, Texas 79762

Location of Well

UNIT LETTER C 1443 FEET FROM THE West LINE AND 10 FEET FROM

THE North LINE, SECTION 5 TOWNSHIP 18-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, GR, etc.)

3963.7' GL 3974.2 RKB

16. Indicate Type of Lease State ☒ Fee ☐
17. State Oil & Gas Lease No. <u>B-1502</u>
18. Unit Agreement Name <u>East Vacuum Grayburg-San Andres Unit</u>
19. Form of Lease Name <u>East Vacuum Grayburg-San Andres Unit, Tract 0524</u>
20. Well No. <u>001</u>
21. Field and Pool, or Willcat <u>Vacuum Grayburg/San Andres</u>
22. County <u>Lea</u>

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☒
CASING TEST AND CEMENT JOB ☒
OTHER Total Depth ☒

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 10-12-79 MI Cactus Drlg. Spudded w/17-1/2" hole, drld to 350' @ 8:30 P.M.
10-13-79 Ran 13-3/8" csg, 48#, H-40 and 54.5#, K-55. Cmt w/675 sxs C1 "H" w/2% CaCl₂ and 1/4# Flocele. Circ 125 sxs. Csg set at 350'. WOC 4-1/2 hrs, temp cmt 65°, formation temp in zone 65°, cmt strength at time of csg test 1500 PSI, cmt in place prior to test 12-1/2 hrs.
10-14-79 Test BOP's and csg OK. Drld ahead w/11" bit to 1711'. Drld ahead w/7-7/8" hole.
10-24-79 Reached TD 4805'.
10-27-79 Ran 5-1/2", 14#, K-55 csg set at 4800'. Cmt w/1500 sxs TLW 12# salt, 10% D.D., 1/4# Flocele, 3# Gilsonite sx followed by 450 sxs C1 "H", 8# salt sx. Circ 200 sxs cmt. Job complete. Released rig. Prep perf.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE November 2, 1979

Orig. Signed by
John Runyan
Geologist

APPROVED BY _____ TITLE _____ DATE NOV 6 1979

CONDITIONS OF APPROVAL, IF ANY: