

Petroleum Information.

© Copyrighted Reproduction Prohibited

COUNTY LEA FIELD Maljamar STATE NM 28
 OPER CITIES SERVICE CO. API 30-025-26462
 SEC 7 LEASE SMGSAU Tr. 5 MAP
Sec 29, T17S, R33E COORD
2615' FNL, 2615' FEL of Sec 4-1-11 NM
11 mi W/Buckeye SPD 12-7-79 CMP 3-4-80

8 5/8" at 1300' w/660 sx 6 1/2" at 3888' w/800 sx 4" lnr 3696-4379' w/50 sx 2" at 4354'	WELL CLASS: INIT D FIN DO ELEV L & S			
	FORMATION	DATUM	FORMATION	DATUM
	ID	4380' (SADR)	PBD	4371'

SP (San Andres) Perfs 4172-4354' P 186 BOPD + 88 BW. Pot
 based on 24 hr test. GOR 180; gty 33

CONFP OERSELEV 4070' GL PD 4380' RT

F.R. 9-17-79

(San Andres)

12-11-79 Drlg 2700' Anhy & salt

12-17-79 TD 3888'; WOCT

1-7-80 TD 3888'; MICT

1-15-80 TD 3888'; SI

1-22-80 TD 4380'; WOC

1-29-80 TD 4380'; PBD 4371'; Tstg

Perf (San Andres) 4305-10', 4324-54' w/2 SPF

Swbd 4 BO + 12 BW in 1 hr 30 mins (4305-54')

2-4-80 TD 4380'; PBD 4371'; SI

Acid (4305-54') 5000 gals

Swbd 21 BO + 50 BW in 10 hrs (4305-54')

2-6-80 TD 4380'; PBD 4371'; SI

2-15-80 TD 4380'; PBD 4371'; Flwg Ld

Set RBP @ 4280'

Perf (Premier) 4172-84', 4204-18', 4224-34'

4248-62', 4268-78' w/2 SPF

4-1-11 NM

4-15-80 Continued
Acid (4172-4278') 5000 gals
Flwd 5 BO + 20 BW in 2 hrs (4172-4278')
Frac (4172-4278') 30,000 gals + 51,000# sd
Flwd 177 BLW w/tr oil in 10 hrs thru 1" chk,
TF 25# (4172-4278')
4-25-80 TD 4380'; PBD 4371'; SI
Fulled RBP @ 4280'
4-30-80 TD 4380'; PBD 4371'; WOSP
Fpd 186 BO + 88 BW in 24 hrs (4172-4354')
4-31-80 TD 4380'; PBD 4371'; Complete
LOG TOPS: Premier 4172', San Andres 4262'
Rig Released 12-15-79
4-1-80 COMPLETION ISSUED

4-1-11 NM

IC 30-025-70352-79