

SUPPLEMENTAL DRILLING DATA

GENERAL EXPLORATION COMPANY

PEANZOIL FEDERAL NO. 1

2180' FSL & 660' FEL, SEC. 1, T-19-S, R-~~33~~-E

LEA COUNTY, NEW MEXICO

This supplemental plan is submitted with the application to drill the above-described well in compliance with NTL-6 of the United States Department of the Interior.

1. The surface is composed of a loamy sand; quaternary in age.
2. Estimated top of primary geologic markers are:

<u>Formation</u>	<u>Estimated Depth</u>
Yates	3,250'
San Andres	5,050'
Delaware	5,770'
Bone Spring	7,550'
Wolfcamp	10,700'
Strawn	12,000'
Atoka	12,255'
Morrow Sand	12,845'
M. Morrow Sand	13,000'
L. Morrow Sand	13,100'
Total Depth	13,400'

Elevations: GL - 3,776'. KB - 3,794' (estimated).

3. The estimated depths at which anticipated water, oil or gas bearing formations are to be encountered are:

5,060'	salt water	San Andres
9,600'	oil	Bone Spring
10,700'	oil/gas	Wolfcamp Lime
12,000'	gas	Strawn
12,255'	gas	Atoka
12,845'	gas	Morrow Sand