

UNIT STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICA
(Other instructions on
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC060967

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

SMGSAU

8. FARM OR LEASE NAME

TRACT #1

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

MALJAMAR (G-SA)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 30, T-17S R-33E

12. COUNTY OR PARISH

LEA

13. STATE

NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☒ GAS ☐
WELL WELL OTHER

2. NAME OF OPERATOR

CITIES SERVICE COMPANY

3. ADDRESS OF OPERATOR

P. O. BOX 1919, MIDLAND, TEXAS 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface2490' From South Line, 1595' From East Line of Section
30, T-17S, R-33E, Lea County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4050.4' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) Commence Drilling ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent
to this work.)*

T.D. 1300'

Set 21' of 13-3/8" conductor pipe and set at 32'. Cemented with 3 yards of Redi-mix. Spudded well 12-17-79. Drilled to 1300'. Set 1286.38' (32 joints) of 8-5/8" OD 24#, K55, ST&C casing at 1300'. Cemented casing with 460 sx Halco lite w/2% CaCl and 1/4# Flocele/sk followed by 200 sx Class C w/2% CaCl. PD @ 1745 MST, 12-19-79. Cement circulated. Float Held OK. WOC 12 hrs. Tested casing and BOP to 2000#/30 mins - OK.

RECEIVED

DEC 31 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Mgr.

DATE 12-27-79

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

GR Hall
JAN 03 1980U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

G.P.O. : 1973-780-622 /VIII-148

RECEIVED

JAN 8 1980

OIL CONSERVATION DIV