

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

COPY TO O. C. C

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

3. LEASE DESIGNATION AND SERIAL NO.

NM 0997

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Querecho

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 28, T-18S, R-33E

12. COUNTY OR PARISH

Lea

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

2. NAME OF OPERATOR
Southland Royalty Company

3. ADDRESS OF OPERATOR
1100 Wall Towers West, Midland, TX 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
1980' FSL & 1980' FWL, Sec. 28, T-18 S, R-33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3783.3' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud, set csg, test csg

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spud well by Hondo Drilg Co. Rig #4 @ 1:00 P.M., 12-2-79. Drill 17½" hole to 370'.
Run 13 3/8" 48# H-40 ST&C csg set @ 370'. Cement w/ 375 sx Class "C" Cement w/ 2% Calcium
Chloride. Circulate cement to surface. Plug down @ 9:30 P.M., 12-2-79. WOC 18 hrs. Nipple
up BOP.

After 24 hrs. WOC test BOP and csg to 1000# for 30 min. Hold OK.

Compressive strength of Class "C" w/ 2% CC after 24 hrs is 2275 psi @ 95° F.

Drill ahead 11" hole.

RECEIVED

DEC 18 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Engineer

DATE 12-11-79

ACCEPTED FOR RECORD

(For office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

DEC 18 1979

U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

*See Instructions on Reverse Side