

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOCC-HOBBS
1-R.J. STARRAK-TULSA
1-A.B. CARY-MIDLAND
1-PJB, ENGR.

1-BB-OFC TECH
1-BH, FLD CLK
1-HC, FOREMAN
1-FILE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR RE-LOCATE TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO DRILL OR RE-ENTER FOR SUCH PROPOSALS.)		5a. Indicate Type of Lease State ☒ Fee ☐
1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER		5. State Oil & Gas Lease No.
2. Name of Operator GETTY OIL COMPANY		7. Unit Agreement Name
3. Address of Operator P. O. BOX 730, HOBBS, NEW MEXICO 88240		6. Form of Lease Name HOBBS "N"
4. Location of Well UNIT LETTER H 1980 FEET FROM THE NORTH LINE AND 330 FEET FROM EAST THE 8 LINE, SECTION 8 TOWNSHIP 18-S RANGE 35-E N.M.P.M. VACUUM ABO REEF		9. Well No. 5
15. Elevation (Show whether DF, RT, GR, etc.) 3946.6 G.L.		10. Field and Pool, or Wildcat VACUUM ABO REEF
12. County LEA		

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐ TEMPORARILY ABANDON ☐ PULL OR ALTER CASING ☐ OTHER ☐	PLUG AND ABANDON ☐ CHANGE PLANS ☐ OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-9-80 Drilled 7-7/8" hole to 9208'. Ran 42 Jts. 5-1/2" 17# and 185 Jts. 5-1/2" 15.5# Casing and set @ 9206'. Howco Guide shoe @ 9205'; Howco Float Collar @ 9161' and Howco DV Tool @ 5982'. Western Co. cemented as follows:

FIRST STAGE: 1350 sxs. Class "H" w/50/50 Poz, 1/4# Cello Seal, .5% TF-4 Mix @ 14.2# and 400 Sxs. Class "H" w/1/4# Cello Seal, 1.25% CF-9, and 2% KCl Mix @ 15.6#. Plug down @ 10:30 P.M.

Dropped Bomb - Opened DV Tool @ 11:15 P.M. w/1200#. Circulated approximately 150 sxs. Cement.

SECOND STAGE: 2100 Sxs. Pacesetter Lite (65% Class "C", 25% Poz Mix & 6% Gel) w/1/4# Cello Seal/Sk. Tailed in w/150 Sxs. Class "C" Neat. Mix @ 14.8#. Plug down @ 5:00 A.M.
3-10-80. With 142 Bbls. Water @ 3000# circulated approximately 50 sxs. Cement. WOC.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE AREA SUPERINTENDENT DATE 3-10-80

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: